



Solmer

SOLTECH LTD.

368-2, SANMAKDONG, YANGSAN,
KYOUNGNAM, 626-120, KOREA.

TEL : 82 55 387 6468
FAX : 82 55 387 6470
E-MAIL : th.choi@uvpia.com
URL : <http://www.uvpia.com>

Aliphatic Urethane Acrylate

SU 522B

Descriptions

SU 522B is a hexa-functional aliphatic urethane acrylate oligomer developed for UV/EB cure coating applications requiring fast curing, high gloss and non-yellowing properties.

Features

- Good hardness and abrasion resistance.
- Good solvent resistance.
- High gloss and light color.
- Non-yellowing.

Specifications

- Viscosity (mPa.s, 60°C)	1,200 ~ 1,800
- Color (Gardner)	2 Max
- Density (g/cm ³)	1.20
- Molecular weight	1,000
- Functionality	6
- Polymer solid % by weight	100

Applications

- Method : spray, screen,
roll and curtain coating.
- Substrate : plastics, wood
- Wood coatings and fillers.
- Scratch resistance on plastics.

Handling

Storage :

Avoid continuous staying over than 40°C
Handle with care and avoid unnecessary personal contact.

Avoid contact with eyes and prolonged or repeated skin contact.

Avoid continuous or repetitive breathing of dust.