



Solmer

SOLTECH LTD.

368-2, SANMAKDONG, YANGSAN,
KYOUNGNAM, 626-120, KOREA.

TEL : 82 55 387 6468

FAX : 82 55 387 6470

E-MAIL : th.choi@uvpia.com

URL : <http://www.uvpia.com>

Aliphatic Urethane Acrylate

SU 543

Descriptions

SU 543 is a difunctional aliphatic urethane acrylate oligomer developed for UV/EB cure coating applications requiring excellent adhesion on difficult substrate, good toughness and non-yellowing properties.

Features

- Good flexibility.
- Excellent adhesion on difficult substrate.
- Excellent durability.
- Good toughness and abrasion resistance.
- Non-yellowing.

Specifications

- Viscosity (mPa.s, 60°C)	100 ~ 300
- Color (Gardner)	2 Max
- Density (g/cm ³)	1.11
- Molecular weight	1,000
- Functionality	2
- Polymer solid % by weight	100

Applications

- Method : spray, screen, roll and curtain coating.
- Substrate : plastics, wood, metal and paper.
- Clear coating for cork.
- Screen ink binder.
- Pigment coating for wood.
- Metal and plastic coatings.

Handling

Storage :

Avoid continuous staying over than 40°C
Handle with care and avoid unnecessary personal contact.

Avoid contact with eyes and prolonged or repeated skin contact.

Avoid continuous or repetitive breathing of dust.