



Solmer

SOLTECH LTD.

368-2, SANMAKDONG, YANGSAN,
KYOUNGNAM, 626-120, KOREA.

TEL : 82 55 387 6468
FAX : 82 55 387 6470
E-MAIL : th.choi@uvpia.com
URL : <http://www.uvpia.com>

Aliphatic Urethane Acrylate

SU 574B

Descriptions

SU 574B is a trifunctional aliphatic urethane acrylate oligomer with 1,6-hexanediol diacrylate. This product is characterized good abrasion and stain resistance, good flexibility, toughness and non-yellowing properties.

Features

- Good abrasion and stain resistance.
- Good flexibility and toughness.
- Good surface curing.
- Light color.
- Non-yellowing.
- Good durability.

Specifications

- Viscosity (mPa.s, 60°C)	1,600 ~ 2,000
- Color (Gardner)	2 Max
- Density (g/cm ³)	1.10
- Molecular weight	2,000
- Functionality	3
- Polymer solid % by weight	86
- HDDA % by weight	14

Applications

- Method : spray, screen,
roll and curtain coating.
- Substrate : plastics, wood.
- Wood flooring and plastics coating.
- Overprint varnishes and screen inks.
- Clear coatings.
- Light stable coatings.

Handling

Storage :

Avoid continuous staying over than 40°C
Handle with care and avoid unnecessary
personal contact.

Avoid contact with eyes and prolonged or
repeated skin contact.

Avoid continuous or repetitive breathing of
dust.